



EN

Flat steel rod **VOLTASTEEL FLAT COVERED** ø 10 mm, covered with PP, with **interchangeable** terminals, complete of flexible starting spinner with eyelet and starting spinner with eyelet.

D

Flachstahl Band **VOLTASTEEL FLAT COVERED** ø 10 mm, mit PP-Ummantelung, mit **austauschbaren Endstücken**; Federführungskopf mit Öse und Zugkopf mit Öse.

E

Pasacables **VOLTASTEEL FLAT COVERED** ø 10 mm, de hilo plano de acero recubierto de PP, con cabeza guía flexible y anilla de enganche, terminales **intercambiables**.

F

Tire-fils **VOLTASTEEL FLAT COVERED** ø 10 mm, en acier avec gaine en PP, avec des terminaux, tête flexible et embout **interchangeables**.

I

Sonda passacavi **VOLTASTEEL FLAT COVERED** ø 10 mm, in piatto armonico rivestito in PP, con terminali fissi **intercambiabili**, completa di testa flessibile con asola e ogiva iniziale con asola.

art.	ø mm	RAL	m	kg
GVAPR10RIC40	10	5015	40	7,30
GVAPR10RIC50			50	9,10
GVAPR10RIC60			60	10,80
GVAPR10RIC70			70	12,70
GVAPR10RIC80			80	14,40
GVAPR10RIC90			90	16,40
GVAPR10RIC100			100	18,00
GVAPR10RIC120			120	21,60



ø 10,0 mm	ø 63-150 mm	++	800 mm	1900 kg	800 kg
40-90 (+ 3÷5) m					