



[EN] Starting spinner with shackle and M5 thread [D] Anfangsbirne M5 mit Schäkel [E] Cabeza guía M5 con grillete de enganche [F] Embout M5 avec manille [I] Ogiva iniziale M5 con grillo d'aggancio

art.	ø mm	gr
GVFOOGGR	23	22

[EN] Starting roller made of aluminium alloy with M5 thread [D] Anfangsbirne mit Führungsrolle M5 aus Aluminium [E] Cabeza guía M5 con rueda de aleación ligera [F] Ogive M5 avec de roues en aluminium [I] Ogiva M5 con rotella di scorrimento in alluminio

art.	ø mm	gr
GVFOOGRO	25	23

[EN] Rotating supple coupling with M5 thread [D] Verbindungshülse mit Drehwirbel, M5 [E] Acoplamiento giratorio con rosca M5 [F] Accoupleur tournant M5 [I] Giunto snodato girevole, M5


art.	ø mm	L mm	gr
GVM5GG	11	31	7

[EN] Galvanised steel cage, vertical version with reel ø 330 mm; fit for 20-80 m of Fiberglass rod ø 4,5 mm [D] Verzinkte Stahlhaspel in stehender Ausführung mit Korbdurchmesser ø 330 mm; Fassungsvermögen 20-80 m Glasfaserstab ø 4,5 mm [E] Contenedor vertical de acero zincado ø 330 mm, para guía pasacables ø 4,5 mm, con capacidad entre 20 y 80 metros [F] Enrouleur en acier galvanisé vertical pour sonde en fibre de verre ø 4,5 mm, d'une longueur de 20 à 80 mètres [I] Aspo raccoglitore in acciaio zincato, esecuzione verticale con ruota ø 330 mm; capienza sonda passacavi ø 4,5 mm da 20-80 m

art.	ø mm	kg	
GVA45	330	3,0	20/30/40/50/60/70/80 m

[EN] Small accessories bag for vertical steel cages [D] Kleine Zubehörtasche für stehende Stahlhaspeln [E] Bolsa pequeña de accesorios para contenedores verticales de acero [F] Sac petite d'accessoires pour enrouleurs verticaux en acier [I] Borsa accessori piccola per aspi verticali in acciaio zincato

art.	
BNACCS	230/110 x 90 x 40 mm



[EN] Starting spinner with shackle and M6 thread **[D]** Anfangsbirne M6 mit Schäkkel
[E] Cabeza guía M6 con grillete de enganche **[F]** Embout M6 avec manille **[I]** Ogiva iniziale M6 con grillo d'aggancio

art.	M	ø mm	gr
GVFOOGGR	5	23	22
GVSOGGR	6	23	19

[EN] Starting roller made of aluminium alloy with M6 thread **[D]** Anfangsbirne mit Führungs-rolle M6 aus Alluminium **[E]** Cabeza guía M6 con ruedas de aleación ligera **[F]** Ogive M6 avec de roues en aluminium **[I]** Ogiva M6 con rotella di scorrimento in alluminio

art.	M	ø mm	gr
GVFOOGRO	5	25	23
GVSOGRO	6	25	26

[EN] Rotating supple coupling with M6 thread **[D]** Verbindungshülse mit Drehwirbel mit Innengewinde M6 **[E]** Acoplamiento giratorio con rosca M6 **[F]** Accoupleur tournant M6 **[I]** Giunto snodato girevole con filetti M6

art.	M	ø mm	L mm	gr
GVM5GG	5	11	31	7
GVM6GG	6	13	35	12

[EN] Cable pulling grip, M5 thread **[D]** Kabelziehstrumpf, M5 **[E]** Malla tiracables, M5 **[F]** Chaussette, M5 **[I]** Calza tirafili, M5

art.	ø mm	L mm		N° wires	ø wire
GVGCT1215AM5	12-15	350	450 kg	2	0,75
GVGCT1519AM5	15-19	350	1300 kg	2	0,75
GVGCT1925AM5	19-25	400	1300 kg	2	0,75
GVGCT2531AM5	25-31	400	1700 kg	2	0,75

[EN] Cable pulling grip, M6 thread **[D]** Kabelziehstrumpf, M6 **[E]** Malla tiracables, M6 **[F]** Chaussette, M6 **[I]** Calza tirafili, M6

art.	ø mm	L mm		N° wires	ø wire
GVSCT1215AM6	12-15	350	450 kg	2	0,75
GVSCT1519AM6	15-19	350	1300 kg	2	0,75
GVSCT1925AM6	19-25	400	1300 kg	2	0,75
GVSCT2531AM6	25-31	400	1700 kg	2	0,75

[EN] Pulling-pushing grip for ø 3-6 mm rod **[D]** Einziehhilfe für ø 3-6 mm Band **[E]** Tirador para guía pasacables ø 3-6 mm **[F]** Poignée de tirage pour tire-fils ø 3-6 mm **[I]** Tappo tiratore per sonda ø 3-6 mm

art.	gr
GVTT7016N	16