

STANDARD, REINFORCED EYE

[EN] Cable pulling grip with two eyes and thimble, long version [D] Kabelziehstrumpf lang, mit zwei Kauschen [E] Malla tiracables con doble lazo y dedales [F] Chaussette tire-câbles à boucle double avec cosse coeur, version longue [I] Calza tiracavi lunga, con due asole con redancia

art.	ø mm	L mm	L ₁ mm				n.			kg
JST215/15	10-15	1700	1500	3.000 daN	4	1,50 mm		7	14 x 24	0,42
JST215/20	15-20	1700	1500	3.000 daN	5	1,50 mm		7	14 x 24	0,45
JST215/30	20-30	1700	1500	3.000 daN	5	1,50 mm		7	14 x 24	0,50
JST215/40	30-40	1700	1500	3.500 daN	6	1,50 mm		7	14 x 24	0,55
JST215/50	40-50	1700	1500	3.500 daN	6	1,50 mm		7	14 x 24	0,60
JST215/60	50-60	1700	1500	3.500 daN	6	1,50 mm		7	14 x 24	0,64
JST215/70	60-70	1700	1500	4.100 daN	7	1,50 mm		7	15 x 29	0,68
JST215/80	60-80	1700	1500	4.700 daN	8	1,50 mm		7	15 x 29	0,70
JST215/80	70-80	1700	1500	4.700 daN	8	1,50 mm		7	15 x 29	0,72
JST215/90	80-90	1700	1500	4.700 daN	8	1,50 mm		7	15 x 29	0,75
JST215/100	80-100	1700	1500	9.400 daN	8	2,00 mm		7	15 x 29	0,80
JT215/100	90-100	1700	1500	9.400 daN	8	2,00 mm		7	18 x 32	1,07
JST215/110	90-110	1700	1500	9.400 daN	8	2,00 mm		7	18 x 32	1,17
JT215/110	100-110	1750	1500	11.000 daN	10	2,00 mm		7	18 x 32	1,22
JST215/120	100-120	1750	1500	11.000 daN	10	2,00 mm		7	18 x 32	1,28
JT215/120	110-120	1750	1500	11.000 daN	10	2,00 mm		7	18 x 32	1,35
JST215/130	120-130	1750	1500	11.000 daN	10	2,00 mm		7	21 x 38	1,42
JST215/150	120-150	1750	1500	11.000 daN	10	2,00 mm		7	21 x 38	1,47
JST215/140	130-140	1750	1500	14.000 daN	12	2,00 mm		7	21 x 38	1,52
JT215/150	140-150	1750	1500	14.000 daN	12	2,00 mm		7	21 x 38	1,58

