



EN

Steel wire rod **VOLTASTEEL WIRE COVERED**, covered with PA, with **interchangeable** terminals **M5**, complete of flexible starting spinner with eyelet and starting spinner with eyelet.

D

Stahldraht **VOLTASTEEL WIRE COVERED** mit PA Um-mantelung, mit **austauschbaren Endstücken M5**; Federführungskopf mit Öse und Zugkopf mit Öse.

E

Guía pasacables **VOLTASTEEL WIRE COVERED** con núcleo de hilo de acero recubierto de PA, con cabeza guía flexible y anilla de enganche, terminales **intercambiables, M5**.

F



Tire-fils **VOLTASTEEL WIRE COVERED** avec âme en fil d'acier, gaine en PA, avec des terminaux, tête flexible et embout **interchangeables, M5**.

I

Sonda passacavi **VOLTASTEEL WIRE COVERED** con anima in filo d'acciaio rivestito in PA, con terminali fissi **intercambiabili M5**, completa di testa flessibile con asola e ogiva iniziale con asola.

art.	ø mm	 ø mm	m	gr
GVVSW405	4	2,5	5	215
GVVSW410			10	410
GVVSW415			15	610
GVVSW420			20	800
GVVSW430			30	1190

art.	ø mm	 ø mm	m	gr
GVVSW505	5	2,75	5	258
GVVSW510			10	490
GVVSW515			15	730
GVVSW520			20	960
GVVSW530			30	1430

						
4	ø 10-32 mm	++	150 mm	580 kg	130 kg	5-30 (+ 3÷5) m
5	ø 12-32 mm	++	160 mm	640 kg	130 kg	10-30 (+ 3÷5) m