

Subject to technical changes without prior notice. Technische Änderungen vorbehalten. Sujeto a variaciones técnicas sin previo aviso. Sujet à des modifications techniques sans préavis. Soggetto a variazioni tecniche senza preavviso.

EN Flat steel rod **VOLTASTEEL FLAT COVERED**, covered with PP, with **interchangeable** terminals, complete of flexible starting spinner with eyelet and starting spinner with eyelet.

D Flachstahl Band **VOLTASTEEL FLAT COVERED** mit PP-Ummantelung, mit **austauschbaren Endstücken**; Federführungskopf mit Öse und Zugkopf mit Öse.








E Guía pasacables **VOLTASTEEL FLAT COVERED** de hilo plano de acero recubierto de PP, con cabeza guía flexible y anilla de enganche, terminales **intercambiables**.

F Tire-fils **VOLTASTEEL FLAT COVERED** en acier avec gain en PP, avec des terminaux, tête flexible et embout **interchangeables**.

I Sonda passacavi **VOLTASTEEL FLAT COVERED** in piatto armonico rivestito in PP, con terminali fissi **intercambiabili**, completa di testa flessibile con asola e ogiva iniziale con asola.

art.	ø mm	M		RAL	m	kg
GWSFC410	4	5		5015	10	0,25
GWSFC415					15	0,35
GWSFC420					20	0,45
GWSFC430					30	0,65

art.	ø mm	M		RAL	m	kg
GWSFC615	6	6		5015	15	1,15
GWSFC620					20	1,50
GWSFC630					30	2,25
GWSFC640					40	3,00
GWSFC650					50	3,75
GWSFC660					60	4,80

						
4	ø 10-60 mm	++	450 mm	290 kg	150 kg	15-30 (+ 3÷5) m
6	ø 12-80 mm	++	620 mm	800 kg	360 kg	20-60 (+ 3÷5) m