

STANDARD, LONG



[EN] Cable pulling grip with single eye without thimble [D] Kabelziehstrumpf mit einer Schlaufe [E] Malla tiracables con un lazo sin dedal
[F] Chaussette tire-câbles à boucle simple sans cosse coeur [I] Calza tiracavi con un'asola senza redancia

art.	ø mm	L mm	L ₁ mm				n.		[mm]	kg
JST115/15A	10-15	1650	1500	3.000 daN	5	1,50 mm		7	6 x 100	0,34
JST115/20A	15-20	1650	1500	3.000 daN	5	1,50 mm		7	6 x 100	0,37
JST115/30A	20-30	1650	1500	3.000 daN	5	1,50 mm		7	6 x 100	0,40
JST115/40A	30-40	1700	1500	3.500 daN	6	1,50 mm		7	6 x 150	0,45
JST115/50A	40-50	1700	1500	3.500 daN	6	1,50 mm		7	6 x 150	0,51
JST115/60A	50-60	1700	1500	3.500 daN	6	1,50 mm		7	6 x 150	0,54
JST115/70A	60-70	1700	1500	4.100 daN	7	1,50 mm		7	8 x 150	0,55
JST115/80A	60-80	1700	1500	4.700 daN	8	1,50 mm		7	8 x 150	0,57
JST115/80A	70-80	1700	1500	4.700 daN	8	1,50 mm		7	8 x 150	0,59
JST115/90A	80-90	1700	1500	4.700 daN	8	1,50 mm		7	8 x 150	0,61
JST115/100A	80-100	1700	1500	9.400 daN	8	2,00 mm		7	10 x 150	0,64
JT115/100A	90-100	1700	1500	9.400 daN	8	2,00 mm		7	10 x 150	0,95
JST115/110A	90-110	1750	1500	9.400 daN	8	2,00 mm		7	10 x 200	0,95
JT115/110A	100-110	1750	1500	11.000 daN	10	2,00 mm		7	10 x 200	1,00
JST115/120A	100-120	1750	1500	11.000 daN	10	2,00 mm		7	10 x 200	1,04
JT115/120A	110-120	1750	1500	11.000 daN	10	2,00 mm		7	10 x 200	1,09
JST115/130A	120-130	1750	1500	11.000 daN	10	2,00 mm		7	10 x 200	1,14
JST115/150A	120-150	1750	1500	11.000 daN	10	2,00 mm		7	10 x 200	1,18
JST115/140A	130-140	1800	1500	14.000 daN	12	2,00 mm		7	12 x 200	1,21
JT115/150A	140-150	1800	1500	14.000 daN	12	2,00 mm		7	12 x 200	1,26

