

**JZKVR171KUN****EN**

Cable laying ground roller fit for installations cables with **ø 160 mm** max.

Composed by:

- galvanized steel frame
- running roller made of **Nylon** mounted on shielded ball bearings

D

Kabelverlegerolle zur geradlinigen Verlegung von Kabeln bis zu einem ø von **160 mm**

Bestehend aus:

- verzinkten Stahlrahmen
- Rolle aus **Nylon**, gelagert mittels doppelt geschützter Kugellager

E

Rodillo para colocar cables adecuado para la colocación en línea recta de cables con un ø máx. de **160 mm**

Compuesto de:

- bastidor en acero cincado
- rodillo de deslizamiento en **Nylon** montado sobre cojinetes de esferas apantallados

F

Galet de tirage de câbles convenant pour le tirage rectiligne de câbles du ø de **160 mm** max.

Comprenant:

- un châssis en acier galvanisé
- un galet en **nylon** monté sur roulements à billes blindés

I

Rullo posacavi adatto per la posa in rettilineo di cavi fino al **ø 160 mm** max.

Composto da:

- telaio in acciaio zincato
- rullo di scorrimento in **Nylon** montato su cuscinetti a sfere schermati

Accessories • Zubehör • Accesorios • Accessoires • Accessori

[1] Spare roller comes complete of screwed shaft M12, ball-bearings, nuts and bolts.

[1] Ersatzrolle aus verzinktem Stahl, mit Gewindestift M12, Kugellager, Beilagscheiben und Mutter.


[1] Rodillo de repuesto con perno roscado M12, cojinetes, arandelas y bulones.

[1] Galet de rechange muni d'axe fileté M12, roulements, rondelles et boulons.

[1] Rullo di ricambio, completo di perno filettato M12 cuscinetti, rondelle e bulloni.

[1]**PA****art.**


XRN20015076



245 x 295 x 180 mm



3,2 kg



200 daN



ø 160 mm



ø 76 - 150 x 200 mm